

Dual Mode Precision Plunge Router 3 ¼ HP

493248
TRA 001

Soft Start & Variable Speed

provides the perfect speed for all cutter types

Quick Access Brushes

allows the end user to change worn brushes



Safety Switch Shutter

locks closed in bit-change mode to prevent router being switched on

Side Air Vents

reduce intake of dust into the motor casing when mounted upside-down in a router table

1/2" & 1/4" (EU: 1/2" & 12mm) Collet

for a greater range of bit shank sizes

3-Stage Turret

with direct reading scales for precise pre-set cut depths



Bit Change

through the base, a single wrench bit change is achieved with the automatic spindle lock

Micro Winder

enables continuous fine depth adjustment through the full plunge range

Removable Plunge Spring

for easy bit adjustment when table mounted

Switching from a Plunge to a Fixed Based Router

with rack & pinion adjustment is as simple as pushing a button

Fully Enclosed Guarding

provides maximum protection from the cut zone & assists dust extraction



IN THE BOX

- Table Height Winder
- 1/2" & 1/4" Collet
- Multi-Function Fence
- Collect Wrench
- Manual

FEATURES

- Powerful 3 ¼ HP (15A) electronically controlled motor
- Single switch from plunge to fixed-base router with rack and pinion height adjustment
- 8,000-20,000rpm electronic speed maintenance under load
- Automatic spindle lock for single wrench bit changes
- 3 stage turret with direct reading scales for precise pre-set cut depths
- Soft start and variable speed provides the perfect speed for all cutter types
- Micro winder enables continuous fine depth adjustment

SPECIFICATIONS

Voltage	110-120V 60Hz
Power	3 ¼ HP / 15A (2,100W)
Speed	8,000- 20,000rpm
Collet	1/2" & 1/4"

Plunge Range	0 - 2.6"
Extraction	Dust Extraction Port
Weight	13.2 lbs

