

## Master Anchor

### Features:

- Installs in minutes and lasts a lifetime
- Objects can be easily removed and replaced
- Fire retardant, structural plastic and stainless steel construction
- Handles vector forces 360° and never loosens
- Wingits are rated up to 300 lbs (depending on the application). Millions of installations and no issues
- Wingits utilize a #8 stainless steel screw
- Typical installations include tv mounts, bath accessories, shelving, cabinets, pedestal sinks, dispensers, coat hooks, railings, heavy drapery rods and for most wall mount accessories with a base over 1"
- Assembled Depth: 11". Assembled Height: 6". Assembled Width: 7 ½". Fastener length: 3 ½"



Part No.	Vendor Reference No.	Sold Unit
501700	MAW35-2	Box of 2
501701	MAW35B24	Box of 24
501702	MAW35B100	Box of 100




## Refined Engineered Safety "RES" Bar Fastener

### Features:

- Average time to install a grab bar is less than 10 minutes and lasts a lifetime
- Exceeds all building codes and ADA guidelines
- No blocking or studs needed
- Install a grab bar exactly where you need it
- Handles vector forces 360° and never loosens
- Rated up to 600 lbs in tile and drywall
- Fire retardant and installs completely waterproof in new and existing construction
- 3/4" holes required
- No caulk needed
- Designed for 2" x 3" or larger hollow walls and wall substrates from 1/4" - 1.3" thick
- Assembled Depth: 5 ½". Assembled Height: 3 ½". Assembled Width: 1 ½"



Part No.	Vendor Reference No.	Sold Unit
501703	RESGBW35	Box of 2



## Commercial Standard Grab Bar Wingit

### Features:

- Rated up to 800 lbs in drywall and tile or ¼" tub surrounds
- Heavy duty 18/8 stainless steel
- Fastening systems become waterproof as they are installed into the wall using 3M's best waterproofing adhesive
- Can be installed into wall substrates (tile, drywall, etc.) up to 1 ½" thick
- Easy installation every time. Can use the Wingit Apache200 Drill Bit for precise holes. 1 ¼" hole required
- No caulk needed
- No blocking or studs needed
- Average time to install a grab bar is less than 10 minutes
- Designed for 2" x 4" hollow walls and wall substrates from ¼" - 1 ½" thick
- Exceeds all building codes and ADA guidelines
- Assembled Depth: 3". Assembled Height: 4". Assembled Width: 3"



Part No.	Vendor Reference No.	Sold Unit
501704	GBW40	Each



## Bathroom Accessory Fastener

### Features:

- Allows for quick installation of oval bath accessories and curved shower rods
- Never sagging or loosening
- Quick, water-resistant installations
- Can be installed into any hollow wall substrates (tile, drywall, etc.) up to 1 ¼" thick
- Use Wingits Apache200 ¾" drill bit ceramic wall tile, marble or plaster & lathe, sold separately



Part No.	Vendor Reference No.	Sold Unit
501705	BAW30	Box of 2